In accordance to Annex III of Regulation (EU) Nr. 305/2011

Sustame of appearant and varification of constancy of norfermance

Declaration of performance No. Identification code of the product-type



## LE-H51127-04 **ALUPLAN RADON ALGV E 50 K/D**

## Purpose

Vapour control layer (Radon barrier)

## Name, contact producer

BÜSSCHER & HOFFMANN GmbH	A-4470 (AT) Fabrikstraße 2	Tel.: +43 (7223) 823 23-0
	Web: www.bueho.com	E-Mail: office@bueho.at

Harmonized standard	EN 13970
system3	EN 13970
Systems of assessment and vernication of constancy of performance	

## **Declared performance**

		Harmonized technical
Essential characteristics	Performance	specification
Watertightness	60 kPa	EN 13970
Reaction to fire test	E	EN 13970
Shear resistance of joints	250 N/50mm	EN 13970
Tensile force long./trans.	500/400 (±100/±100)	EN 13970
	N/50mm	
Elongation at single-end breaking force	4/4 (±2/±2) %	EN 13970
Resistance to impact	NPD	EN 13970
Resistance to static loading	NPD	EN 13970
Resistance to tearing (nail shank) long./trans.	180/180 (±50/±50) N	EN 13970
Flexibility at low temperatures	-15 °C	EN 13970
Water vapour transmission	> 1500 m Sd	EN 13970
Water vapour transmission after artifical aging	> 1500 m Sd	EN 13970
Water vapour transmission after exposure to liquid chemicals	NPD	EN 13970
Hazardous substances	None	EN 13970

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by

Var houde

Bmstr. Dipl. Ing. Karl Landl **General Manager** 

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.